

M.2 2280 SSD

IM2P42B8



The ADATA IM2P42B8 PCIe Gen4x4 industrial-grade M.2 2280 SSD is NVMe 1.4 compliant, utilizing 176-layer 3D TLC NAND flash for excellent performance and high capacities, as well as a 3K P/E cycle rating for great durability. What's more, the IM2P42B8 supports a Host Memory Buffer for improved random read/write performance, LDPC ECC (error correction code), RAID Engine, and End-to-End Data Path Protection technology for optimal data integrity. Furthermore, it supports AES 256-bit encryption for improved data security. Thanks to these advantages, the IM2P42B8 is ideal for a wide range of industrial applications, including 5G, AI, networking, automation, server and surveillance.

Features

- PCIe Gen4x4 interface/ NVMe 1.4 compliant
- 176-layer 3D TLC NAND flash for higher capacities and endurance
- 3K P/E cycle rating for great durability and reliability
- Supports Host Memory Buffer
- AES 256-bit Data Encryption
- LDPC ECC error correction, RAID Engine, and End-to-End Data Path Protection
- Complies with ESD (Electrostatic Discharge) IEC/EN 61000-4-2 level 4 standard
- Suitable for 5G, AI, networking, automation, server, and surveillance applications


Ordering Information

Operating Temp.	512GB	1TB	2TB
0°C to 70°C	IM2P42B8-512GCTM4	IM2P42B8-001GCTM4	IM2P42B8-002GCTM4

Specifications

Model	IM2P42B8
Form Factor	M.2 2280
Capacity	512GB – 2TB
Interface	PCIe Gen4x4
Flash Type	176L 3D TLC
Dimensions (L x W x H)	80 x 22 x 3.6mm
Sequential Read (Max.)	5100MB/s
Sequential Write (Max.)	4700MB/s
Operating Temperature (Standard)	0°C to 70°C
Operating Temperature (Industrial)	N/A
Operating Voltage	3.3V
Power Consumption (Max)	4.8W
Shock Resistance	1500G/0.5ms, Half Sine Wave
Operating Humidity	5%-95% RH, non-condensing
Vibration Resistance	20G (20-2000Hz)
Technologies	LDPC ECC, RAID Engine, Wear Leveling, SLC Cache, TRIM Command, Thermal Throttling, S.M.A.R.T. Monitor, AES 256-bit Data Encryption, Host Memory Buffer End-to-End Data Path Protection, ESD Support (IEC/EN 61000-4-2 level 4)

Diagram



Unit: mm

Contact Us

HQ (Taiwan):

T: +886-8228-0886

E: IA_Global@adata.com

US:

T: +1-714-332-8708

E: IASales_us@adata.com

EU:

T: +49-899-0405-296

E: IASales_eu@adata.com

China

T: +86-21-6233-1010

E: IASales_cn@adata.com

JP:

T: +81-3-5807-0011

E: IASales_jp@adata.com

APAC/MEA:

E: IASales_apacmea@adata.com